



### Main

Device short name	MN
Product or component type	Voltage release
Device application	Control
Range compatibility	Masterpact NT Compact NS630b...1600 Compact NS1600b...3200 Masterpact NT NAVY Masterpact NW Masterpact NW NAVY
Offer type	C4 C5
Voltage release type	Undervoltage release
[Uc] control circuit voltage	100...130 V AC 50/60 Hz 100...130 V DC

### Complementary

Threshold tripping voltage	0.35...0.7 Un opening 0.85 Un closing
Supply holding power	4.5 VA
Mounting mode	Fixed
Response time	40 ms (Masterpact NT) 90 ms (Masterpact NW)
Accessory / separate part category	Spare parts for Masterpact NT Spare parts for Masterpact NW Spare parts for Compact NS1600b...3200 Spare parts for Compact NS630b...1600

### Offer Sustainability

Sustainable offer status	Green Premium product
--------------------------	-----------------------

REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>

### Contractual warranty

Warranty	18 months
----------	-----------