
voltage release XF - 200..250 V DC/AC 50/60 Hz



		۷.
Device short name	XF	- t
Product or component type	Voltage release	<u>.</u>
Device application	Control	
Range compatibility	Masterpact NT Masterpact NW	for some
[Uc] control circuit voltage	200250 V AC 50/60 Hz 200250 V DC	products

Complementary

Threshold tripping voltage	0.851.1 Un	ie
Supply holding power	4.5 VA	
Mounting mode	Fixed	ability
Response time	55 ms (Masterpact NT)	
•	70 ms at 800 A (Masterpact NW)	, in
	70 ms at 1000 A (Masterpact NW)	Ē
	70 ms at 1250 A (Masterpact NW)	<u> </u>
	70 ms at 1600 A (Masterpact NW)	ي
	70 ms at 2000 A (Masterpact NW)	——————————————————————————————————————
	70 ms at 2500 A (Masterpact NW)	S
	70 ms at 3200 A (Masterpact NW)	o O
	70 ms at 4000 A (Masterpact NW)	oo t
	80 ms at 4000 A (Masterpact NW)	<u>ଅ</u>
	80 ms at 5000 A (Masterpact NW)	a p
	80 ms at 6300 A (Masterpact NW)	, i

Contractual warranty

	•		
Warranty		18 months	