



Schneider
Electric

SIEMENS

LS ELECTRIC

HYUNDAI

CH35
Ideal Selection Best Solution

CHINT

Autonics
Sensors & Controllers

SHIVA Amvaj

آدرس : تهران ، خیابان لاله زار نو، بالاتر از خیابان منوچهری، مجتمع تجاری البرز ۲۰ ، طبقه اول ، واحد ۲۳۵
تلفن : ۹۲ - ۰۲۱-۶۶۳۴۱۰۹۰ فروشگاه اینترنتی : www.peoe.ir

@peoe_iran

peoe_iran

Top 100
Global
Innovator
for 10 years



Micro Drive M100

The Best Way to Save Money and Time

■ Built-in C2 EMC Filter

■ User-Friendly Design

- DIN rail mountable
- Side-by-side installation
- Easy connection with RJ45 port
 - Modbus / Smart copier / Remote keypad / Driveview9

■ New UL 61800-5-1 Design

- Enhanced isolation circuit

■ Built-in DB Unit : $\geq 1.5\text{kW}$

■ Modbus in Advanced I/O Type




Built-in EMC Filter (C2 class)



Side-by-side Installation
(2mm between drives)



DIN rail Mountable




Smart Copier
(Parameter copy without power)



1 Phase 100~120V 0.2~0.75kW
1 Phase 200~240V 0.1~2.2kW



LSELECTRIC



Specification


		1 Phase 100~120V			1 Phase 200~240V					
Division		0002	0004	0008	0001	0002	0004	0008	0015	0022
Applied Motor	Heavy Duty									
	HP	0.25	0.5	1.0	0.125	0.25	0.5	1.0	2.0	3.0
	kW	0.2	0.4	0.75	0.1	0.2	0.4	0.75	1.5	2.2
Rated Output	Rated Capacity (KVA)	0.6	0.95	1.9	0.3	0.6	0.95	1.9	3.0	4.5
	Rated Current (A)	1.4	2.4	4.2	0.8	1.4	2.4	4.2	7.5	10.0
	Frequency (Hz)	0~400Hz			0~400Hz					
	Voltage (V)	3 phase 200~240V			3 phase 200~240V					
Rated Input	Rated Current (A)	3.7	7.4	13.9	1.0	1.8	3.7	7.1	13.6	18.7
	Frequency (Hz)	50~60Hz (±5%)			50~60Hz (±5%)					
	Voltage (V)	1 phase 100-120Vac (-15% to +10%)			1 phase 200-240Vac (-15% to +10%)					
	Cooling Type	Natural cooling			Natural cooling			Forced fan cooling		
Weight (Kg)		1			0.66			1		
								1.45		

Environment

Ambient Temperature*1)	-10~50°C (14~122°F), Ambient temperature under the condition of no ice or frost
Ambient Humidity	Relative humidity less than 95% RH (to avoid condensation forming)
Storage Temperature	-20~65°C (-4~149°F)
Surrounding Environment	Environment Level: 3C3(IEC60721-3-3) classifications (for SO ₂ , H ₂ S, CL, NO ₂) No corrosive gas, flammable gas, oil mist and dust etc., indoors
Altitude/Oscillation	Below 1,000m, below 9.8m/sec ² (1G)
Pressure	70~106kPa

*1) 0.1~0.2kW products can be operated at a maximum of 50°C. However, the lifespan of the product maybe reduced when operating continuously with a full load when the ambient temperature exceeds 40°C

I/O Configuration



Dimension

	W	H1	H	D
1 Phase 100~120V				
0002M100-S	85 (3.34)	163 (6.42)	153 (6.02)	123 (4.84)
0004M100-S	100 (3.94)	190 (7.48)	180 (7.08)	140 (5.51)
1 Phase 200~240V				
0001M100-1	85 (3.34)	145 (5.70)	135 (5.31)	100 (3.93)
0002M100-1	85 (3.34)	163 (6.42)	153 (6.02)	123 (4.84)
0004M100-1	100 (3.94)	190 (7.48)	180 (7.08)	140 (5.51)
0015M100-1	100 (3.94)	190 (7.48)	180 (7.08)	140 (5.51)
0022M100-1	100 (3.94)	190 (7.48)	180 (7.08)	140 (5.51)

Seoul Office

LS Yongsan Tower, 92, Hangang-daero, Yongsan-gu, Seoul, 04386, Korea
Tel: 82-2-2034-4644(Europe), 4982(USA), 4884(East Asia)
Fax: 82-2-2034-4588 E-mail: drivesales@ls-electric.com



According to The WEEE Directive, please do not discard the device with your household waste.