

به ایران پس از رستم پیلتن سرافراز لشکر منم ز انجمن

Piltan

باتری ایرانی هژیر صنعت

- ✓ باتری VRLA با تکنولوژی AGM
- ✓ بدون نیاز به نگهداری، عاری از هرگونه بخارات اسیدی در محیط
- ✓ قابلیت شارژ و دشارژ پذیری به دفعات
- ✓ گارانتی معتبر
- ✓ طول عمر طراحی شده ۱۰ سال (Design Life)
- ✓ دارای استانداردهای 2018 : ISO 45001 ، 2015 : ISO 9001 CE
- ✓ کاربرد در تجهیزات صنعتی، الکترونیکی، مخابراتی و پزشکی



Piltan

باتری پیلتن

Model	HP 12280		LHP 1242		LHP 1265	
Volts	12V		12V		12V	
Capacity (25 °C)	20 hours rate (1.4A)	28Ah	20 hours rate (2.0A)	40Ah	10 hours rate (6.5A)	65Ah
Discharge Current	20 I ₂₀ rate (28A, 27min)	38min	20 I ₂₀ rate (40A, 27min)	35min	1 hours rate (35.7A)	36Ah
Testing (25 °C)	60 I ₂₀ rate (84A, 7min)	9min	60 I ₂₀ rate (120A, 7min)	8min	3 hours rate (16.2A)	49Ah
Internal Resistance	Full Charged Battery 25°C	8.5mΩ	Full Charged Battery 25°C	8mΩ	Full Charged Battery 25°C	6.3mΩ
Capacity Affected By Temperature	40°C		104%			
	25°C		100%			
	0°C		83%			
	-15°C		65%			
Residual Capacity (25 °C)	Capacity After 3 Months Storage		91%			
	Capacity After 6 Months Storage		82%			
	Capacity After 12 Months Storage		65%			
Charge (Constant Voltage)	Cycle (25°C) Initial Charging Current Less Than 8.4A Voltage 14.5~14.9V		Cycle (25°C) Initial Charging Current Less Than 12A Voltage 14.5~14.9V		Cycle (25°C) Initial Charging Current Less Than 19.5A Voltage 14.5~14.9V	
	Float (25°C) Charge Voltage 13.6~13.8V					
Weight (Approx)	8.8Kg		12.6Kg		19.8Kg	

